

Building Mount
6", 10-1/2" or 14" Dia.
Corridor
Walkways
Accent
Building Entrances



BL-36



BL-37



BL-35



BL-38



BL-39

Specifications



Certifications The fixture shall be ETL and CETL listed for wet location.

Ballast Housing Cast aluminum with a minimum thickness of 1/8". Mounting plate welded to ballast housing for J-box mounting. Housing is fully gasketed with 3/16" extruded EDPM cord gasket.

Lens Frame Cast aluminum mounted to ballast housing with 8-32 or 10-24 stainless steel flat head screws.

Lens Opal UV-stabilized polycarbonate (OP) is standard. Lens supplied with closed cell EPDM gasket (BL-35), and a one-piece extruded silicone gasket (BL-36/37/38/39).


Ballast Fluorescent ballasts for 42CFT and 2-D lamps are electronic (minus 20° C). Other fluorescent 13- through 26-watt quad tube is core & coil (0° C).

Finish BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

BL

PROJECT
FIXTURE TYPE
CATALOG#

BL-35/36 37/38/39

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Lens	Finish ¹	Options
BL-35	10 Watt 2-D	10W-2D	120	OP Opal Polycarbonate	BK Black	EMG ³ Emergency Battery Backup
BL-36	(2) 18 CFQ	CFQ ²	120		BZ Bronze	
BL-37	21 Watt 2-D	CFT ²	208		WH White	
	70 MH	E17	240		GR Green	
	70HPS	E17	277		NA Natural Aluminum	
BL-38	(2) 26 CFQ	CFQ ²			GY Gray	
BL-39	38 Watt 2-D	F382D			CC Custom Color	
	42 CFT	CFT ²			NA Natural Aluminum	
	100 MH	E17				
	100 HPS	E17				

¹ Consult factory for other colors and voltages

² CF = single biax, CFQ = double biax, CFT = triple biax

Luminaire Dimensions

Luminaire	A		B		Weight	
	Inch	mm	Inch	mm	lbs.	kg
BL-35	6.00	152	6.00	152	8	3.6
BL-36	10.50	267	7.00	178	11	5.0
BL-37	10.50	267	6.50	165	11	5.0
BL-38	14.00	356	7.50	190	15	6.8
BL-39	14.00	356	7.00	178	15	6.8

